



# IY90 & IY125

SOFTMOUNT WASHER-EXTRACTOR

FOR ON-PREMISES LAUNDRY APPLICATIONS

INDUSTRIAL  
BY DESIGN

## Dependable

- Stainless steel drum, tub and cabinet
- Bearing house in cast iron out of 1 piece:
  - » No bolts or welds
  - » Long life span
- Suspension: shock absorbers and springs
- Extra strong door hinge
- Ozone compatible seal system
  - » Keeps out humidity and water from the bearings
  - » Keeps the grease in the bearings

## Efficient

- Perforated lifting ribs provide more mechanical action for superior wash quality
- Standard inverter drive
  - » Washing and spin speed freely programmable
  - » Smooth transition from wash to spin cycle
  - » High G-Force (up to 350G)
  - » Low sound level
- Dual drain valves
  - » Attached to the frame directly under the tub: lower water consumption
  - » 90° drain valve: auto-rinsing effect behind the valve
  - » Water re-use is possible
- Eco washing programs – significantly reduces water and electricity consumption

## Intuitive

- Aries Elite
  - » Fully Programmable
  - » 99 programs
  - » Multi-lingual
  - » Networking available
  - » USB connection on back panel for easy programming
- Panels easily removable for quick access to all parts
- Very large door opening for easy loading & unloading
- Practical soap dispenser
  - » 5 compartments
- 8 liquid soap signals



ERGONOMICAL  
CONSTRUCTION



LARGE DOOR  
OPENING




LOW WATER  
CONSUMPTION



LOW ENERGY  
CONSUMPTION

# SOFTMOUNT WASHER-EXTRACTOR

Specifications	IY90	IY125
Control	Micro	Micro
Capacity - lb (kg)	90 (40)	125 (55)
Dimensions	-	-
Width - in (mm)	47 (1195)	47 (1195)
Depth - in (mm)	56 1/2 (1430)	63 3/8 (1610)
Height - in (mm)	75 (1905)	75 (1905)
Cylinder Diameter - in (mm)	36 (914)	36 (914)
Cylinder Depth - in (mm)	24 (610)	31 1/8 (790)
Cylinder Volume - cu. ft. (liters)	14.1 (400)	18.3 (518)
Door Opening Size - in (mm)	21 5/16 (540)	21 5/16 (540)
Door Bottom to Floor - in (mm)	28 3/4 (730)	28 3/4 (730)
Wash Speed - RPM	38	38
Extract Speed - RPM	830	830
Extract G-Force	350	350
Water Inlet Conn. - in (mm)	3 x 1 (25)	3 x 1 (25)
Steam Inlet Conn. - in (mm)	3/4 (19)	3/4 (19)
Drain Conn. Size - in (mm)	2 x 3 (76)	2 x 3 (76)
Motor Size - HP (kW)	10.06 (7.50)	10.06 (7.50)
Voltage/Hz/Phase Circuit/	220-240V 50-60Hz 3ph 400-480V 50/60Hz 3ph	220-240V 50-60Hz 3ph 400-480V 50/60Hz 3ph
Shipping Dimensions	-	-
Height - in (mm)	82 15/16 (2105)	82 15/16 (2105)
Width - in (mm)	56 5/16 (1430)	56 5/16 (1430)
Depth - in (mm)	61 13/16 (1570)	68 7/8 (1750)
Net Weight - lb (kg)	3439 (1560)	3594 (1630)
Shipping Weight - lb (kg)	3748 (1700)	3902 (1770)
Agency Approvals	CSA	CSA



For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Czech facility has been registered to ISO 14001:2005 and 9001:2009.

©Copyright 2016 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC  
Shepard Street  
Ripon, WI 54971